


Product Technical Data Sheet - Nylon Dome Top Glands



Durable Nylon (Polyamide 66) dome top cable glands.
Available in a range of sizes and colours.

Supplied complete with a locknut and sealing washer
to achieve IP68.



Part Reference	Hole Size	Colours	Cable Diameter (mm) C	Overall Length* (mm) L	Thread Length (mm) T	Pack Quantity
DTGM16	M16		5 to 10	34	10	10
DTGM20	M20		6 to 12	35	10	10
DTGM20ET	M20		6 to 12	40	15	10
DTGM20B	M20		10 to 14	35	10	10
DTGM25	M25		13 to 18	45	12	10
DTGM32	M32		18 to 25	51	12	1
DTGM40	M40		25 to 32	60	17	1
DTGM50	M50		30 to 38	70	18	1
DTGM63	M63		37 to 44	74	20	1

* Length before compression.

Specification.

Gland and Locknut: Nylon PA66. UL94V-2(0)
Sealing Washer: Nitrile Rubber
Temperature Range: -40°C to 100°C
Ingress Protection: IP68

Meets the requirements of:
(Low Voltage Directive 2014/35/EU)
BS EN 62444:2013 Cable glands
for electrical installations
CE Marked.

For use with round cables.



Partex Marking Systems (UK) LTD

61-64 Station Road, Coleshill, Birmingham B46 1JT

Tel: 01675 463670 Fax: 01675 463520 Email: sales@partex.co.uk



Issue 2
March 2024

www.partex.co.uk

