

# PLTC

- Tape, permanent or removable
- Continuous form
- Print with thermal transfer printer
- Perfect for component marking



## BENEFITS

A soft and flexible universal tape, for indoor and outdoor use.

Vinyl tape is characterized by high adhesion and is the perfect solution for rough surfaces and irregular shapes. The durable acrylic adhesive allows the tape to be used on a variety of surfaces, including stainless steel and glass.

The most significant advantage and potential of the PLTC label is its continuous form, which enables to design and print labels of any length. Available in different heights.

Print the continuous tape in requested length via EOS or MK10 thermal transfer printer and Partex software Promark Creator.

## TECHNICAL INFORMATION

### Material

Vinyl

### Temperature range

-40°C to +80°C

### Min application temperature

+2°C

### Resistance

Excellent resistance to moisture, alcohols and oil.  
UV resistant material.

### Colors

Standard colors: white (9) and yellow (4).  
Others on request: black (0), brown (1), red (2), orange (3), green (5), blue (6), purple (7), silver (8) and transparent (T).

### Adhesive

Acrylic adhesive

### Expiry date

24 month at +21°C and 50% RH.

## PRODUCT INFORMATION

Article number	Description	Height mm	Packaging m/reel
PLTC009000D9VR	Tape, removable	9	100
PLTC009000D*VP	Tape, permanent	9	100
PLTC012000D*VP	Tape, permanent	12	100
PLTC018000D*VP	Tape, permanent	18	100
PLTC025000B*VP	Tape, permanent	25	60
PLTC050000D*VP	Tape, permanent	50	30
PLTC100000D*VP	Tape, permanent	100	30

\* Color. Yellow=4, White=9 (standard colors)

PARTEX.NU

