



Product Data Sheet - PVMC4-1500 Solar Connector

Robust impact and UV resistant housing, with a secure crimp connection.
Designed for use with photovoltaic PV modules, inverters,
and solar power installations.

Supplied as a complete four part kit to ensure perfect compatibility.



Dimensional Data:



Specification.

Temperature Range:	-40°C to 85°C
Rated Voltage:	1500V DC
Current rating:	30A
Contact Resistance:	0.25m
Ingress Protection:	IP68 (Mated)
Cable Size:	2.5 - 6.0mm ²
Flammability Class:	UL94-V0

Materials.

Body:	Nylon PA66. UL94V-0
Contacts:	Tin Plated Copper.

Partex PVMC4-1500V meets the requirements of:

IEC 62852:2020 (Class II of IEC 61140:2001)
UL6703:2014
IEC 61984:2008 & UL 1977
TÜV Certified

Associated Products:

PVMC4-1500-TOOL Installation Tool
CT-MC4 Ratchet Crimping Tool



Partex Marking Systems (UK) LTD

61-64 Station Road, Coleshill, Birmingham B46 1JT

Tel: 01675 463670 Fax: 01675 463520 Email: sales@partex.co.uk



Issue 1
Dec 2024

www.partex.co.uk